

## VOLTAGE TESTER SERIES „ProCleanTech“

### 3038

#### CAT IV / 1000 V

- AC/DC Voltage tester  
12...1000 V AC and  
12...1500 V DC
- LED Display
- Continuity test function with optical  
and acoustical indication
- Integrated single pole test
- Rotary field indication
- Integrated torch light

### 3039

#### with LED and LCD Display

same as 3038 and also offers:

- LCD Display with backlight



## SCOPE OF SUPPLY

- |   |                                 |
|---|---------------------------------|
| 1 St. HDT Voltage Tester<br>Series „ProCleanTech“ | 1 pc Carton Packaging           |
| 2 pcs Batteries 2 x 1.5V AAA                      | 2 pcs GS38 Probe-tip protection |
| 1 pc Instruction Manual                           | 2 pcs 4mm test tips adapter     |

## VOLTAGE TESTER SERIES „ProCleanTech“

### TECHNICAL DATA

Model	3038	3039
Anzeige	13 LEDs	13 LEDs, 4 Digit LCD
Voltage range	LED: $\pm 12, 24, 50, 120, 230, 400, 690, >1000$ V	LED: $\pm 12, 24, 50, 120, 230, 400, 690, 1000$ V LCD: 1000 V AC, 1500 V DC
Backlight	n/a	●
Polarity Indication	automatic	
Frequency Range	16...400 Hz	
Input current	< 3,5 mA (690 V AC) < 6 mA (1500 V DC)	
Single pole test	90...1000 V AC	
Rotary field indication	120...1000 V	
Continuity / Diode test	optical and acoustic	
Resistance	–	–
RCD trip test	–	–
Overvoltage category	CAT IV 1000V	
Protection degree	IP 64	
In compliance with	EN 61010, EN 61243-3:2014	
Certification	CE	
Battery test	Connect both tips	LowBat in LCD Display
Battery	2 x 1,5V AAA	
Length of cable	approx. 1,2 m	
Dimension	approx. 240 x 75 x 30 mm	
Weight	ca. 270 g	



Universal cap



Integrated torch light



Switchable load (3037)