

EVSE WALLBOX FUNCTION TESTER 8140

CAT II / 300 V



FEATURES

- Type-2 plug to connect directly to EVSE charging point
- Rotary field indicator between phases L1, L2 and L3 with phase indication with LEDs
- 4 position slider switch to simulate CP mode A, B, C and E
- Rotary field indication without battery
- Warning in case of wrong wiring
- The fixed Type-2 plug enables quick and easy testing
- 230 / 400 V AC 3~ 50 / 60 Hz
- CAT II / 300 V

SCOPE OF SUPPLY

- 1 pc HDT 8140
- 1 pc Instruction Manual
- 1 pc Carton Packaging



TECHNICAL DATA

Model	8140
Phase	LED display L1, L2, L3
Rotary field Indicator	LED display „R“, „L“
Warning Indicator	LED
Max. Input Voltage	230 / 400 V AC 3~ 50 / 60 Hz
Operating Time	continuous
Duration time	≤ 3,5 mA
Overvoltage Category	CAT II / 300 V
Pollution degree	2
Temperature Range	0...40°C
Altitudes above SL	≤ 2000 m
Protection degree	IP 40
In compliance with	IEC / EN 61010-1, IEC / EN 61557-7, IEC / EN 611010-031
Dimension (approx.)	600 x 70 x 60 mm
Weight (approx.)	365 g